

SKY LOCKS

Sky Lock III Secondary Brake

Weight: 12 lbs. Use on: CX1250

> Alpha 1000 Compact 750 Model 4 hoists

Part #: 56009839

Sky Lock II Secondary Brake

Weight: 15 lbs. Use on Alpha 1500

Alpha 800 hoists

Part #: 56009826



ky Lock is a registered trademark of the Sky Climber independent, secondary safety brake. Offered in two models, the Sky Lock II and the Sky Lock III provide additional back up to those safety features already built into all Sky Climber hoists.

The Sky Lock does not require any outside power sources to operate. It senses the speed of the wire rope as it travels through the hoist. If the wire rope speed exceeds the factory preset level, the Sky Lock automatically locks onto the wire rope and will support the entire load.

OSHA requires an independent secondary brake such as the Sky Lock to be attached to every hoist sold and operated. ALL Sky Climber hoists come complete with the Sky Lock attached.

Sky Locks may also be used as an independent brake, a descent or overspeed control device on oil drilling rigs, or as auxiliary brakes on special purpose elevators.

Links, Nuts and Bolts ARE required for each hoist/Sky Lock attachment.

These links, nuts and bolts are not included with the hoist at the time of shipment. Make sure to order the following parts and quantities

Hoist	Sky Lock	Part #	Links	Bolts	Nuts
CX1250's	Type III	56009839	(1) 600-7	(1) 107-856 (2) 107-328	(1) 107-130
Compact 750's	Type III	56009839	(2) 600-7	(1) 107-856 (2) 107-328	(1) 107-130
Alpha 1000's	Type III	56009839	(2) 305-395	(3) 107-130	(3) 107-328
Alpha 1500's	Type II	56009826	(2) 305-395	(3) 107-130	(3) 107-328

Protective Canvas Covers for Hoists and Sky Locks



Hoist Cover

For Alpha 1000 Compact 750 CX1250

Part #: 42008106

For Alpha 1500 Part #: 41008150



Sky Climber Inc. 1501 Rock Mountain Blvd. Stone Mountain, GA 30083 USA

770/939-7705 phone 770/493-7392 fax

info@skyclimber.com

800/255-4629 toll free Sky Climber equipment meets or exceeds requirements made by agencies such as OSHA, CSA and CE.

