



**LNX**™ The durable and rugged standard for man rated hoists.



**SKY CLIMBER**  
ACCESS INNOVATIONS SINCE 1955











Modular design and construction.  
 Internal Sky Lock  
 Easy to access  
 Side panel removes easily



Emergency ascent handwheel, shown in stored position.  
 Sealed worm gearbox drives solid sheave  
 Sits flat on work bench for easy maintenance and storage  
 Central control box and pendant ready  
 Designed to work well on low voltages



Fewer wear parts  
 Less maintenance  
 Lower cost of ownership

# LNXTM Specifications

Lifting Capacity	1000, 1250, 1500 lbs
Voltage	185 to 220 Volts
Durable Outer Shell	Cast Aluminum
Phase	Single and Three
Hertz	50 and 60
Dual Rope Capacity	Optional
Internal Secondary Brake	Yes
Motor Type	1.9 HP
Worm Gear Box	Yes
Amperage	9.0
Weight	105 lb.
Upper Limit Switch	Optional
Ultimate Upper Limit Switch	Optional

Emergency Stop	Yes
Rope Easily Accessed	Yes
Non-Powered Control Descent	Yes
Manual Ascent Handle Attached	Yes
Overspeed Indicator	Yes
Self Reeving	Yes
Stow Away Stirrup Strap	Yes
Overload Protection	Optional
Solid Sheave Traction Mechanism	Yes
Central Control Box Capable	Yes
Labor Required for Maintenance	< 1 Hour
Wire Rope	5/16" or 8mm
Low Voltage Indicator	Optional



24 Months factory warranty on all parts and labor.



36 Months on all geartrain parts and labor.



[www.skyclimber.com](http://www.skyclimber.com)

1800 Pittsburgh Drive, Delaware, OH USA 43015 Ph: (740) 203-3900 Toll-free: (800) 255-4629 [info@skyclimber.com](mailto:info@skyclimber.com)

Nijverheidsstraat 23, 2570 Duffel, Belgium Ph: +32 (0)3 887 81 20 [info@skyclimber.be](mailto:info@skyclimber.be)

Authorized Dealer